

DCNM-DVT

www.bo h t . o



S

S

S

S

S

S

•

•

•

•

•

•

S



•

•

-

-

-

-

-

v

()

•

•

-

•

•

•

•

-

-

•

-

-

-

-

•

•

•

•

3.

0.4

2

J4



	/
CE	DECL E C DCNM-DVT



1	DCNM DVT DICENTIS
---	-------------------



	48 VDC
	3.7 W
	100 Hz – 20 kHz -3 dB
THD	< 0.1 %
	> 90 dB
	> 90 dB

	80 dB	IEC60914
	110 dB	IEC60914

	72 dB	0.5
	87 dB	
	0 dBV	
	3 dBV	
	> 32 ohm< 1k ohm	
	65 mW	

NFC	ISO/IEC14443 A 106 kbps 848 kbps MIFARE 106kbps
-----	---

x x	72 x 259 x 139 2.8 x 10.2 x 5.5 (RAL 9017)
	955 2.1

	5 °C +45 °C 41 °F +113 °F
	-30 °C +70 °C -22 °F +158 °F
	< 90 % > 5%



DCNM-DVT

S
DCNM-DVT

DCNM-HDMIC

S S S
DCNM-HDMIC

DCNM-MICS

S S S
DCNM-MICS

DCNM-MICL

S S S
DCNM-MICL

DCNM-TC D

10 DCNM-xD
0 S 0
0
DCNM-TC D

ACD-MFC-ISO

MIFAREclassic 1kB 50pcs
2 0 /
ACD-MFC-ISO

ACD-EV1-ISO

MIFARE EV1 8kB 50pcs
2 S V 0 /

ACD-EV1-ISO

DCNM-LSID

S
S

S
S

ØÑ ô