

# DICENTIS

cn.boschsecurity.com



u  
u  
u  
u  
u

(IEEE802.3) OMNEO

5

DICENTIS

DICENTIS

DICENTIS  
DICENTIS

- LED
- 
- 

- 3 XLR
- 4 RCA
- 3 XLR
- 4 RCA
- 

- 1 RJ45
- 3 (144 W) RJ45
- 1 (15 W) RJ45



- 
- LED
- 
- LED

1 DCNMAPS2DICENTIS

	100 240 Vac 50 60Hz
	530W
DCNM	48Vdc
	3x144W+ 15W

	30Hz - 20kHz
THD	< 0.1 %
	> 95dB
	> 95dB

XLR	-18dBV (+6dB / -18dB)
XLR	+18dBV
	-30dBV (+6dB / -18dB)
	+6dBV

XLR	-18dBV (+8 / -24dB)
XLR	+20dBV
	-30dBV (+8 / -24dB)
	+8dBV

	19	
x x		
	92x440x400 3.6x17.3x15.7	
19	88x483x400 3.5x19x15.7	
	40	1.6
	360	14.2
	7.62	16.79
	RAL 9017 RAL 9022	

:  
333  
: 200335  
: +86 21 22181111  
: +86 21 22182388  
www.boschsecurity.com.cn

:  
11 5  
506-509  
:+852 2635 2815  
:+852 2648 7986  
www.boschsecurity.com.cn